

PRODUCT DATA SHEET

Avery Dennison® MPI™ 1105 Wrapping series

Issued: 07/2021

Introduction

Avery Dennison MPI 1105 Wrapping series films are gloss white, premium quality self-adhesive cast vinyls. The films are ultra-conformable and opaque, and offer excellent durability and conformability. Combined with a DOL 1460 Z / 1470 Z / 1480 Z series overlamine, Avery Dennison MPI 1105 Wrapping films are highly recommended for applications on rivets and corrugations. In addition, MPI 1105 Wrapping films are available with Easy Apply RSTM technology with the air-egress feature and maximum slideability and repositionability.

Conversion

MPI 1105 Wrapping films are ultra-premium products, delivering maximum durability for a wide range of graphics applications. The films are suitable for use on a variety of super-wide format inkjet printers using solvent, eco solvent, UV or latex ink.

To enhance colour and to protect images against UV radiation and abrasion, it is recommended to protect Avery Dennison MPI 1105 Wrapping films using an overlamine - Avery Dennison DOL 1460 Z Gloss or Avery Dennison DOL 1480 Z Matt conformable overlaminates.

For recommended combinations of DOL films and media, please refer to "Technical Bulletin 5.3". Recommended combinations of Avery Dennison Overlaminates and Avery Dennison Digital Print Media". For information on how to apply Avery Dennison MPI Cast Films, please refer to "Technical Bulletin 5.9. Application methods for Avery Dennison Cast Films".

MPI 1105™ in combination with one of the DOL 1400 Z Series overlamine finishes, can also be applied in more critical areas such as gas stations or tank trucks. For more information please refer to Technical Bulletin 5.16 - Application of Avery Dennison® MPI 1105™ with contact to petrol

Recommendations

- » Large fleet graphics on flat, curved, riveted and corrugated surfaces
- » Vehicle wrapping applications
- » Interior & exterior signs
- » Durable advertising, requiring clean removal after the intended period of use

Features

- » Superb 3D conformability for demanding vehicle and fleet wrapping projects
- » Faster, easier installation with Avery Dennison Easy Apply RS technology
- » Stunning and consistent image quality on a variety of printers using solvent, eco solvent, UV or latex inks
- » Clean long-term removability after years of usage
- » Maximum outdoor durability, up to 10 years unprinted
- » ICS Performance Guarantee
- » HP Latex Certified



Face Film

50 micron gloss white cast vinyl



Adhesive

Permanent, acrylic based with grey tie coat and long term removability properties



Backing

MPI 1105 Gloss Two side PE coated StaFlat™ paper, 155g/m2

MPI 1105 EA RS Gloss Two side PE coated StaFlat™ paper, 155g/m2



Durability

10 years (unprinted, vertical exposure)



Shelf Life

2 years

Physical Characteristics

	Test method ¹	Results
Product		
Caliper, facefilm (micron)	ISO 534	50
Caliper, facefilm + adhesive (micron)	ISO 534	80
Opacity		> 99%
Dimensional stability (mm max.)	FINAT FTM 14	0.4
Shelf life (years)	Stored at 22° C/50-55 % RH	2
Durability ² (years)	Unprinted, vertical exposure	10
Fire Classification Rating	EN13501-1	B-s1, d0
Adhesive		
Elongation (%)	DIN 53455	200
Adhesion, initial (N/m)	FINAT FTM-1, stainless steel	MPI 1105: 300 MPI 1105 EA RS: 280
Adhesion, after 24 hours (N/m)	FINAT FTM-1, stainless steel	MPI 1105: 650 MPI 1105 EA RS: 420
Temperature range		
Application temperature (Minimum: °C)		≥10 °C
Service temperature (°C to +°C)		- 40 °C to + 80 °C
Chemical properties³		
Chemical resistance	Mild acids	No effect
Solvent resistance	Mild alkalis	No effect
Solvent resistance	Applied to aluminium	No effect exposed to: oils, greases, aliphatic solvents, motor oils, heptane, kerosene and JP-4 fuel.

Important

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

1) Test methods: More information about our test methods can be found on our website.

2) Durability: The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.

3) Prolonged immersion in gasoline and similar fluids is not recommended.

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>.

Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.

© 2022 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.