

---

## Product Data Sheet

4M CL PET HTC/ R8001/ 2M CL PET(After Market)

**Product code : MZ1001C**

Issue date: 2014-03-17

### Facestock:

100mic Clear PET HTC is a specially engineered hard coat applied polyester film. (For after-market application, this product has protective layer of 50mic Clear PET on top)

Caliper: 105 mic. (±10%) ISO 534  
Basis Weight: 147 g/m<sup>2</sup> (±10%) ISO 536

### Adhesive:

R8001 is specially modified ultra-removable silicone adhesive, suitable for flat gloss substrate, featuring excellent clarity, wet-out performance and heat stability over broad range of temperature in removability without adhesive stain on a broad range of substrates over long period of time.

Min. appl. temp.: ↑ -30℃  
Service temp.: -73℃ ~ +250℃  
Peel Adhesion 8g/in FTM #2

### Liner:

2M CL PET is a 50mic Clear polyester film liner featuring good dimensional stability for die cutting and stable release.

Caliper: 50 mic (±10%) ISO 534  
Basis Weight: 75 g/m<sup>2</sup> (±10%) ISO 536

N.B. All data to be considered as typical values

---

### Applications and use:

This product is suitable for use in a wide range of LCD, LED and mobile phone protective applications.

RoHS & Halogen Free

### Printing/Converting:

This product can be die-cut and stripped on standard web-fed presses.

### Shelf life:

1 year when stored at 22℃ at 50% RH

### Statement of Practical Use:

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

---

#### Avery Dennison Roll Materials Korea



<b>Seoul</b> Tel: +82 2 3406 6200 Fax: +82 2 3406 6210	<b>Daegu</b> Tel: +82 53 581 8645 Fax: +82 53 581 8647	<b>Busan</b> Tel: +82 51 262 9001 Fax: +82 51 262 9013	<b>Anyang</b> Tel: +82 31 361 0240 Fax: +82 31 454 8481
--	--	--	---

---

### Warranty

Information concerning Products are based upon tests believed to be reliable but do not represent a guarantee or warranty. Products are provided on the basis that any Purchaser has independently determined the suitability of the Products and Purchaser's purposes. The Company warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year of delivery (but not afterwards), upon notification thereof within seven (7) days of such appearance and substantiation that the Products have been stored and applied in accordance with the Company standards, the Company shall within a reasonable period correct such defects by providing a suitable replacement without charge at the Company's plant or at the location of the Products (at the Company's election) provided however, if the Company in its sole discretion determines that replacement is not commercially practical, the Company may issue a credit in favour of the Purchaser in an amount not to exceed the purchase price actually paid for the Products. Any implied warranty of merchantability fitness for particular purpose or other warranty of quality, whether express or implied by law, is hereby excluded to the extent permitted by law. In no event shall the Company be liable for any incidental, indirect or consequential damages including, but not limited to, loss of profit, loss of use or loss of capital. The remedies of the Purchaser set forth herein are exclusive, and the total potential liability of the Company arising out of any contract of or from the manufacture, sale, delivery, resale, installation or use of any products shall not exceed the purchase price of the products upon which liability is based.