
Product Data Sheet

38 CL PET TC/ R0302N/ 2M WH PET

Product code : MZ1004A

Issue date: 2014-03-17

Facestock:

38 CL PET TC is a print receptive top coated polyester film featuring excellent UV printability and clarity. Specific testing is required.

Caliper: 38 mic. (±10%) ISO 534
Basis Weight: 50 g/m² (±10%) ISO 536

Adhesive:

R0302N is industrial grade ultra removable acrylic adhesive, featuring good clarity, excellent wet-out performance and excellent heat stability over broad range of temperature in removability without adhesive stain on a broad range of substrates over long period of time.

Min. appl. temp.: ↑ 5°C
Service temp.: -20°C ~ 80°C
Peel Adhesion ↓ 15g/in FTM #2

Liner:

2M WH PET is a 50mic siliconised WHITE polyester film liner featuring good dimensional stability for die cutting and stable release.

Caliper: 50 mic (±10%) ISO 534
Basis Weight: 70 g/m² (±10%) ISO 536

Applications and use:

This product is suitable for use in a wide range of LCD, LED and mobile phone OEM, gloss plastic Work-in-process protective film application.

RoHS & Halogen Free

Printing/Converting:

The top-coating is featuring superior printing quality in UV letterpress, Flexo, UV Offset and ribbon printing. Testing is highly recommended to ensure satisfactory toner anchorage and print results with specific ribbons. This product can be die-cut and stripped at high speeds on standard web-fed presses.

Shelf life:

1 year when stored at 22°C at 50% RH

Statement of Practical Use:

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

Avery Dennison Roll Materials Korea



Seoul

Tel: +82 2 3406 6200
Fax: +82 2 3406 6210

Daegu

Tel: +82 53 581 8645
Fax: +82 53 581 8647

Busan

Tel: +82 51 262 9001
Fax: +82 51 262 9013

Anyang

Tel: +82 31 361 0240
Fax: +82 31 454 8481

Warranty

Information concerning Products are based upon tests believed to be reliable but do not represent a guarantee or warranty. Products are provided on the basis that any Purchaser has independently determined the suitability of the Products and Purchaser's purposes. The Company warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year of delivery (but not afterwards), upon notification thereof within seven (7) days of such appearance and substantiation that the Products have been stored and applied in accordance with the Company standards, the Company shall within a reasonable period correct such defects by providing a suitable replacement without charge at the Company's plant or at the location of the Products (at the Company's election) provided however, if the Company in its sole discretion determines that replacement is not commercially practical, the Company may issue a credit in favour of the Purchaser in an amount not to exceed the purchase price actually paid for the Products. Any implied warranty of merchantability fitness for particular purpose or other warranty of quality, whether express or implied by law, is hereby excluded to the extent permitted by law. In no event shall the Company be liable for any incidental, indirect or consequential damages including, but not limited to, loss of profit, loss of use or loss of capital. The remedies of the Purchaser set forth herein are exclusive, and the total potential liability of the Company arising out of any contract of or from the manufacture, sale, delivery, resale, installation or use of any products shall not exceed the purchase price of the products upon which liability is based.