

Fasson® 60# Cast Gloss/R128/40#SCK

Spec# 07607

Facestock:

The new Fasson® 60# Cast Gloss is a bright, blue-white cast-coated gloss paper featuring high strength and excellent ink receptivity. Prints well with flexo, letterpress, screen, and offset ink systems.

Basis Weight:	60# per ream \pm 10% (500 sheets 25" x 38")
Caliper:	0.0035 inches \pm 10%
Tensile:	MD 28# per inch width CD 15.4# per inch width
Tear:	MD 57 grams per sheet CD 55 grams per sheet
Stiffness:	MD 124 mg CD 75 mg

Adhesive:

Fasson® R128 is a general purpose removable rubber-based adhesive with high initial tack, internal strength, and stable adhesion. With the exception of HDPE substrates, R128 is recommended where clean removability is of primary importance. Can be used on a variety of substrates including glass, metal, plastic, and others. Fasson® R128 adhesive is suitable for applications where compliance with FDA 175.105 is required. This sections covers applications where incidental contact between food and adhesive could occur.

Type:	Hot melt rubber
Minimum Application Temperature:	+10° F
Service Temperature Range:	-65° F to +120° F

Typical Performance Data: 60# C1S Paper at room temperature on standard lab panels

Stainless Steel

Loop Tack: 1.7 lbs
Peel Adhesion: 0.4-0.7 lbs

Treated LDPE

Loop Tack: 1.3 lbs
Peel Adhesion: 0.3-0.6 lbs

Glass

Loop Tack: 1.3 lbs
Peel Adhesion: 0.4-0.7 lbs

Liner:

40#SCK is a bleached super-calendered kraft stock featuring high internal strength, toughness, and tear resistance. Used primarily for roll-to-roll label applications.

Basis Weight: 40.70# per ream \pm 10%
(500 sheets 24" x 36")
Caliper: 0.0025 inches \pm 10%
Tensile: MD 34# per inch width
CD 22# per inch width
Tear: MD 32 grams
CD 34 grams

Total Construction Caliper (approximate): 0.0068 inches \pm 10%

Applications and Uses

This product is suitable for a wide variety of labeling applications where excellent print quality and adhesive removability are critical. Fasson® R128 can be used for promotional labels and is ideal for cassette labeling. Its high internal strength allows for superior converting compared to our other rubber-based removable adhesives.

Shelf Life

Unless specified otherwise in this document, one year when stored at 72°F at 50% RH

Statement of Practical Use

All pressure-sensitive materials should be tested thoroughly under end-use conditions to ensure they meet the requirements of the specific application.

Warranty

All sales and contracts for sale are expressly conditioned on the buyer's assent to Avery Dennison's terms and conditions found on its website at www.na.fasson.com. Avery Dennison hereby objects to any term, different from or additional to Avery Dennison's terms, contained in any buyer communication in any form, unless agreed to in a writing signed by an officer of Avery Dennison.

www.na.fasson.com



Label and Packaging Materials-North America

8080 Norton Parkway
Mentor, OH 44060
800-944-8511