

Fasson® 60# Cast Gloss/R5195/40#SCK

Spec# 18445

Facestock:

The new Fasson® 60# Cast Gloss is a bright, blue-white cast-coated gloss paper featuring high strength and excellent ink receptivity. Prints well with flexo, letterpress, screen, and offset ink systems.

Basis Weight:	60# per ream \pm 10% (500 sheets 25" x 38")
Caliper:	0.0035 inches \pm 10%
Tensile:	MD 28# per inch width CD 15.4# per inch width
Tear:	MD 57 grams per sheet CD 55 grams per sheet
Stiffness:	MD 124 mg CD 75 mg

Adhesive:

Fasson® R5195 is a general purpose removable adhesive featuring moderate initial tack and minimal adhesion build over time. Its consistent level of adhesion and long term removability make it suitable for applications on substrates such as glass, plastics, and corrugated cardboard. It has also been found to adhere well to curved glass and plastic substrates approaching 1" in diameter; however, use caution with stiff facestocks.

Type:	Emulsion Acrylic
Minimum Application Temperature:	+40° F
Service Temperature Range:	-65° F to +180° F

Typical Performance Data: Tested with 60# C1S Paper at room temperature on standard lab panels.

Glass

Loop Tack:	1.0 lbs avg
Peel Adhesion:	0.9 lbs avg

Corrugated

Loop Tack:	0.5 lbs avg
Peel Adhesion:	0.6 lbs avg

Liner:

40#SCK is a bleached super calendered kraft stock featuring high internal strength, toughness, and tear resistance. Used primarily for roll-to-roll label applications.

Basis Weight:	40.5# per ream \pm 10% (24" X 36" 500 sheets)
Caliper:	0.0024 inches \pm 10%
Tensile:	MD 40# per inch width CD 14.8# per inch width
Tear:	MD 34.7 grams CD 41.8 grams

Total Construction Caliper (approximate): 0.0067 inches \pm 10%

Shelf Life

Unless specified otherwise in this document, one year when stored at 72°F at 50% RH

Statement of Practical Use

All pressure-sensitive materials should be tested thoroughly under end-use conditions to ensure they meet the requirements of the specific application.

Warranty

All sales and contracts for sale are expressly conditioned on the buyer's assent to Avery Dennison's terms and conditions found on its website at www.na.fasson.com. Avery Dennison hereby objects to any term, different from or additional to Avery Dennison's terms, contained in any buyer communication in any form, unless agreed to in a writing signed by an officer of Avery Dennison.

www.na.fasson.com



Label and Packaging Materials-North America

8080 Norton Parkway
Mentor, OH 44060
800-944-8511